


# Outer Frame Options

## Standard door frame options

### Standard version

LB Plastics Sheerframe


- 70mm profile section reinforced
- Weather seal gasket & brush-pile draught seal
- Kitemark to BS EN 12608
- Standard White or woodgrain foil options



### Slimline version

LB Plastics Sheerframe

- 70mm profile section reinforced
- Weather seal gasket & brush-pile draught seal
- Kitemark to BS EN 12608
- Standard White or woodgrain foil options




## Fire rated door frame options

### Standard version

LB Plastics Sheerframe


- 70mm profile section steel reinforced
- Bespoke fire rated frame system to BS 476 pt22
- Steel reinforced
- Kitemark to BS EN 12608
- Standard White or woodgrain foil options



### Hardwood version

Hardwood Fire Frame

- 80mm profile section with 20mm intumescent strip
- From certified source
- Kitemark to BS EN 12608
- Supplied treated and stained, or primed in white



### Please Note

All available with a range of cill options and Building Regulations Approved Compliant threshold systems; see cill and threshold data sheet for sample technical drawings.

Newent Business Park, Newent, Gloucestershire, GL18 1DZ

T +44 (0) 1531 822 585 F +44 (0) 1531 822 586

[www.systembuildingproducts.com](http://www.systembuildingproducts.com)

**Britdoors**  
By **System'**